

CMHT2053F5MP HD Vari-Focal IR Turret Camera



Key Features

- 1/2.5" High-Performance Progressive Scan COMS
- 2560 × 1944 resolution
- 5MP HD Analog Out Put(AHD/TVI/CVI)
- Long distance transmission Up to 400 meters without delay and loss
- Support 2.8 to 12 mm Lens
- Support DNR /DWDR
- Support low illumination, Auto color to black
- Support ICR switch, day & night monitor















Specification

Image Sensor	1/2.5"5MP Progressive Scan COMS
Resolution	2560 x 1944
Image System	PAL/NTSC
Minimum Illumination	Color: 0.01 lux @ (F1.2, AGC ON), 0 lux with IR
Electronic Shutter	PAL: 1/25 s to 1/50,000 s; NTSC: 1/30 s to 1/50,000 s
Lens	2.8 to 12 mm
Horizontal Field of View	38.7 ° to 97 °
SMD	24 pcs
SNR	>52dB (AGC off)
IR distance	40m
Video Frame Rate	5MP/20fps;5MP/12.5fps;4MP 30/25fps;CVBS 30/25fps
Video Output	1HD, TVI/AHD/CVI/CVBS output
D&N	Support ICR EXT/Auto / Color/ BW (Black and White)
White Balance	ATW / MWB
BLC	Support
Image Set	Brightness, sharpness, Digital Noise Reduction
Language	English
Operating Conditions	(-20 °C to 60 °C), Humidity 90% or less (non-condensing)
Protection level	IP66
Power Supply	12VDC;
Power Consumption	Max. 6W (Max. 6W with IR cut filter on)
Dimensions	φ 118.8×83.6mm
Weight	670g














Dimension







© 2018 LT Security, Inc. All Rights Reserved. White papers, data sheets, quick start guides, and/or user manuals are for reference only and may or may not be entirely up to date or accurate based upon the version or models. Product names mentioned herein may be the unregistered and/or registered trademarks of their respective owners









