# **Platinum IP Pinhole Camera**

#### CMIP-PH5



## **Key Features:**

### **Dimensions:**

- · 5MP Resolution
- · Sony CMOS Sensor
- · Onvif Profile S,G
- · 3.7mm Pinhole















## **Platinum IP Pinhole Camera**

#### CMIP-PH5

CAMERA	
Image Sensor	5MP SONY Progressive Scan CMOS Sensor
Signal System	PAL/NTSC
Effective Pixels	2944x1656
Min. Illumination	0.001 Lux @ (F1.2, AGC ON)
Shutter Speed	1/25(1/30)s to 1/10,000s
Lens	3.7mm Pinhole Lens
Synchronization	Internal
Video Frame Rate	5MP @ 20fps / 2MP @25fps
Digital Noise Reduction	2D NR & 3D NR
Protocols	TCP /IP, HTTP/HTTPS/FTP/DHCP/DNS/DDNS/RTP/RTSP/RTCP/NTP/UPnP/SMTP/IPv6
GENERAL	
Working Temperature	-20°C - 60°C (-20°F - 140°F)
/Humidity	90% or less (non-condensing)
Power Supply	POE / 12V DC
Power Consumption	Max 4W
Dimension	40(W) x 28(H) x 40(D) mm
Weight	160g