

Platinum IP Covert Camera


CMIP-PIR



Key Features:

- 5MP Resolution
- Sony CMOS Sensor
- Onvif Profile S,G
- 3.7mm Pinhole

Dimensions:



Platinum IP Covert Camera

CMIP-PIR

CAMERA	
Image Sensor	5MP SONY Progressive Scan CMOS Sensor
Signal System	PAL/NTSC
Effective Pixels	2944x1656
Min. Illumination	0.1 Lux @ (F1.2, AGC ON) or 0.3 Lux @ (F2.3, AGC ON)
Shutter Speed	1/25(1/30)s to 1/10,000s
Lens	3.7mm Lens
Synchronization	Internal
Video Frame Rate	5MP @ 15fps 60HZ /12fps 50Hz
Digital Noise Reduction	2D NR & 3D NR
Protocols	TCP /IP, HTTP/HTTPS/FTP/DHCP/DNS/DDNS/RTP/RTSP/RTCP/NTP/UPnP/SMTP/IPv6
GENERAL	
Working Temperature /Humidity	-20°C - 60°C (-20°F - 140°F)
	90% or less (non-condensing)
Power Supply	POE / 12V DC
Power Consumption	Max 4W
Dimension	69(W) x 126(H) x 50(D) mm
Weight	550g