

Multi-purpose Camera Tester LM4-ITCAA



Key Features:

- Support 8MP IP, 8MP TVI, 8MP CVI, 8MP AHD and Analog camera test
- 4 inch touch screen, 1920×1200 resolution
- H.265/H.264, 4K video display via mainstream
- 5-1 Multi-purpose Camera Tester
- Built in WIFI
- Wrist design, portable and easy to carry

Other Features:

- 10/100/100M Ethernet, network state and traffic display
- Wrist design, portable and easier to carry
- Network tool: PING test, IP address scan, port flashing etc
- Drop-down menu, can select Poe power, IP setting, CVBS, LAN info etc· Self-update software, you can install apps with android version
- Media player, 4K video files and MKV/MP4 media files play
- Display its genuine resolution of the IP camera images
- PTZ control supports more than 30 protocols such as PELCO-P, PELCO-D, and SAMSUNG
- Audio in, support record and save the audio/LED lamp, calculators, music players and other application tools
- 7.4 V /2400mAh Lithium Ion Polymer Battery, after 4~5 hours charging, working time lasts 7 hours

Multi-purpose Camera Tester

LM4-ITCAA

Parameter	
Display	4 inch IPS touch screen , resolution 800 x 480
Network port	10/100/100M Ethernet, network state and traffic display
WIFI	Built in WIFI
IP camera type	LTS,ONVIF, ONVIF PTZ
Camera input	8MP IP camera, 8MP TVI camera, 8MP CVI camera, 8MP AHD camera
Rapid ONVIF	Search camera quickly, auto log in and display image from the camera, activate LTS camera
TVI/CVI/AHD test	
TVI video signal test	8MP TVI camera test, 3840 x 2160P 15 FPS, UTC control & call OSD menu
CVI video signal test	8MP CVI camera test, 3840 x 2160P 12.5/15 FPS, UTC control & call OSD menu
AHD video signal test	8MP AHD test, 3840x2160P 15 FPS, UTC control & call OSD menu
Analog Video test	1 channel BNC Input NTSC/PAL (Auto adapt)
Zoom Image	4 x zoom, to enlarge image, screen snapshot, record, save, view and record and play back
HDMI output	N/A
12V/3A power output	DC12V 3A power out, supply temporarily power for the camera
5V/2A power output	USB 5V 2A power output, as a power bank
PoE power output	48V PoE power output, Max power 24W
Audio test	1 channel audio signal input, test whether sound normal, 1 channel audio signal, to connect headphone
TesterPlay	N/A
Color bar generator	N/A
UTP Cable teste	Test UTP cable connection status and display on the screen. Read the number on the screen
RJ45 cable TDR test	RJ45 cable TDR test, cable quality test
Data monitor	Captures and analyzes the command data from controlling device, also can send hexadecimal
Network test	Link monitor, port flashing, Ping test
PoE test	N/A
Drop-down menu	You can select PoE power switch, IP setting, CVBS, LAN info, etc in any interface
General	
External power supply	DC 12V 1A
Battery	Built-in 7.4V Lithium polymer battery, 2400mAh
Rechargeable	After charging 4~5 hours, normal working time 7 hours
Operation setting	Touch screen, OSD menu, select your desired language
Auto off	1-30 (mins)
Working Temperature	-10 °C ~ +50 °C(14°F - 122°F)
Working Humidity	30%-90%
Dimension	126mm x 83mm x 33mm
Weight	0.7KG