

Mifare Card Reader

LTK1101M and LTK1101MK

Key Features:

- Built-in audible beeper;
- Display the reader status with LED indicator;
- Watchdog design for repairing itself in case that exception occurs, to ensure the long service life of the reader;
- Dust-proof and weather-proof design;
- Equipped with the 32-bit high-speed processor;
- RS485 and Wiegand(W26/W34) protocol;
- DIP switch;
- PC+ABS material shell with PMMA panel design;
- Read Mifare card and obtain the card No.



LTK1101M

LTK1101MK

Properties

Power Supply	DC 12V
Working Current	≤ 500mA
Processor	32-bit
Reading Frequency	13.56MHz
Reading Range	≤ 50mm (≤ 1.97")
ID Settings	via DIP Switch
Audio Alert	Beeper
Power Consumption	≤ 2W
Keypad	No Keypad for LTK1101M; Keypad with 12 Keys (0 to 9, *, #) for LTK1101MK
Certifications	FCC, CE
LED Indicator	Power Indicator; Status LED Indicator
Working Temperature	-4° F to +149° F (-20° C to +65° C)
Working Humidity	10 % to 90 % (Non-Condensing)
Water-proof	IP64
Dimensions	5.20" × 3.63" × 0.81"(132.0mm × 92.3mm × 20.5mm)
Weight	≤ 0.31lb (0.14Kg)
Installing Method	Only applied for 120 Gang Box