

Platinum Enterprise Level 32 Channel NVR 1.5U LTN8932-P16




Key Features:

- Up to 32 network cameras can be connected
- Support live view, storage, and playback of the connected camera with up to the resolution of 12 megapixels
- Up to 16 independent PoE network interfaces for different models
- HDMI Video output at up to 4K (3840 × 2160) resolution
- Up to 4 SATA hard disks can be connected with up to 6TB capacity for each
- Supports HDD quota and group modes

Rear Panel:

- | | |
|----------------------------|--|
| 1. LAN Network Interfaces | 9. Alarm in/out |
| 2. Audio out | 10. GND |
| 3. Audio in | 11. 100~240VAC Power Input |
| 4. HDMI Interface | 12. Power Switch |
| 5. USB 3.0 Interface | 13. eSATA Interface |
| 6. RS-232 Serial Interface | 14. Video out |
| 7. VGA Interface | 15. Network Interfaces with PoE function |
| 8. RS-485 Serial Interface | |



Platinum Enterprise Level 32 Channel NVR 1.5U

LTN8932-P16

Video/Audio Input	
IP video Input	32-CH, Up to 12 MP resolution
Two-way audio input	1-ch, RCA (2.0 Vp-p, 1kΩ)
Network	
Incoming bandwidth	256Mbps
Outgoing bandwidth	256Mbps
Remote connection	128
Video/Audio Output	
Recording resolution	12 MP/8 MP/6 MP/5 MP/4 MP/3 MP/1080p/UXGA/720p/VGA/4CIF/DCIF/2CIF/CIF/QCIF
HDMI output	4K (3840 × 2160)/60Hz, 4K (3840 × 2160)/30Hz, 1920 × 1080p/60Hz, 1600 × 1200/60Hz, 1280 × 1024/60Hz, 1280 × 720/60Hz, 1024 × 768/60Hz
VGA output	1-ch, resolution: 1920 × 1080p/60Hz, 1280 × 1024/60Hz, 1280 × 720/60Hz, 1024 × 768/60Hz
CVBS output	1-ch
Audio output	1-ch, RCA (Linear, 1kΩ)
Decoding	
Live view / Playback resolution	12 MP/8 MP/6 MP/5 MP/4 MP/3 MP/1080p/UXGA/720p/VGA/4CIF/DCIF/2CIF/CIF/QCIF
Synchronous playback	16-CH
Capability	4-ch @ 4K, or 16-ch @ 1080p
Hard Disk	
SATA	4 SATA interfaces for 4 HDDs
Capacity	Up to 6TB for each disk
External Interface	
Network Interface	1 RJ-45 10/100/1000 Mbps self-adaptive Ethernet interface
Serial interface	1 RS-485 (half-duplex), 1 RS-232
USB Interface	Front panel: 2 × USB 2.0; Rear panel: 1 × USB 3.0
Alarm in/out	16/4
PoE	
Interface	16 RJ-45 10/100 Mbps self-adaptive Ethernet interfaces
Max. Power	≤200W
Supported standard	IEEE 802.3 af/at
GENERAL	
Power Supply	100~240V AC
Consumption	≤20 W (without enabling PoE)
Working Temperature	+14 °F~ + 131 °F(-10 °C ~ +55 °C)
Working Humidity	10% - 90%
Casing	19-inch rack-mounted 1.5U casing
Dimensions (WxDxH)	17.5"× 15.3" × 2.8"(445 × 390 × 70 mm)
Weight	≤ 11 lb (5 Kg)