


**6 Core, 14/020 Unshielded Security Cable,
White LSZH Jacket**

NSC6CLSZH300/100



| | | |
|-----------------------|---|---|
| Cable Code | NSC6CLSZH300/100 | |
| Description | 6Core 0.44mm ² Security Cable. 14/0.2 Plain Copper Wire, Oxygen Free Copper. LSZH sheathed Extra Low Voltage, not for mains connection. | |
| Application | For inter-connect wiring, suitable for usage in Security & Intruder alarm systems. Use in low voltage/low current applications such as intercommunications. | |
| 1. Conductor | Material | Stranded Annealed Bare Copper |
| | Construction | 14/0.20mm |
| | Nom. O.D. | 0.86mm |
| | Nom. Cross Section Area | 0.44 mm ² |
| | Max. DCR @ 20C | 44.8 ohm / km |
| 2. Insulation | Nom. O.D. | 1.50mm |
| | Nom. Wall Thickness | 0.32mm |
| | Color code and Lay up | Black / White / Red / Blue / Green / Yellow, 6 cores stranded |
| 3. Sheath | Material | LSZH, White |
| | External O.D. | 5.60±0.20 mm |
| | Nom. Wall Thickness | 0.55±0.05 mm |
| Operating Temp. Range | -40C to 75C | |
| Packing | 300M REEL-IN-BOX | |
| Cable weight | 15 Kg / 300M | |

